

» Features

- Sharp "click" feeling with positive reliability feedback.
- Precise design terminal type adequate for DIP IC pitch size (multiple of 2.54mm).
- Several LED colors options.
- Adequate for DIP & SMT.
- Several cap legends options.

» Applications

- Operating switches in all types of electronic equipment such as audio apparatus, office equipment, communications apparatus, TV sets, VCRs, etc.



» Specifications

Rating	50mA 12VDC
Insulation Resistance	100MΩ Min (at 500 VDC)
Dielectric Strength	AC 250V (50/60 Hz for 1 minute)
Contact Resistance	100mΩ Max. (Initial)
Electrically Life	300,000 Cycles Min
Ambient Temperature	-20°C~ +70°C
Operating Force	160 ± 50gf
Travel	0.25 ± 0.1 mm

» LED Specifications

Color	VR	IF	Recommended Operating Current	VF	
				Nor	Max
Red	DC 5V	20mA	20mA	1.7V	2.4V
Green	DC 5V	20mA	20mA	1.9V	2.4V
Yellow	DC 5V	20mA	20mA	1.9V	2.4V
Blue	DC 5V	20mA	20mA	3.0V	3.6V
White	DC 5V	20mA	20mA	3.0V	3.6V

For the specification about the other LEDs, please contact with sales department

» Product selection

PB 614

BUTTON TYPE		FUNCTION		LED COLOR		LASER ETCHING COLOR		LASER ETCHING	
1F		Non-LED		1	Red	1	Misty Silver	01	
2F		Standard type		2	Yellow	2	Bright Silver	02	
3F		M SMT type		3	Green	3	Gold	03	OK
1		LED		4	Blue	4	White	04	
4		L Standard type		5	White	5	Bright Black	05	
5		ML SMT type		6	Pure Green	6	Red	06	
6				8	Amber	7	Misty Black	07	
8				9	Blue Green	8	Sky blue	08	
9				011	Pink	9	Gunmetal Black	09	
10				12	Red/Yellow	A	Orange	10	
11				13	Red/Green				
12				14	Red/Blue				
13				23	Yellow/Green				
				48	Blue/Amber				
				52	White/Yellow				
				58	White/Amber				
				-	Non-LED				

Please inquire about the details with our sales representative.

PB614 SERIES

LED ILLUMINATED TACT SWITCH





» Operating characteristics

Unit: mm



Dimensions

P.C.B Layout



PB6141FL





PB6142FL



PB6143FL



PB6141L



PB614 SERIES

LED ILLUMINATED TACT SWITCH





» Operating characteristics

Unit: mm



Dimensions

P.C.B Layout



PB6144L





PB6145L



PB6146L



PB6149L-□-102





» Operating characteristics

Unit: mm



Dimensions

P.C.B Layout



PB61410L





PB61411L-□-103



PB61412L-□-104



PB61413L-□-101





» Operating characteristics

Unit: mm



Dimensions

P.C.B Layout



PB61415FL-□-102



PB61416FL-□-5307



PB61417FL-□-6102



PB61422FL-□-850R

