

RJS102P-16L SERIES
LED METAL SWITCH



Product Image	LED Type	Operation	Contact	Model	Material Finishes	LED Colour	Rated Voltage/Current
	With LED	Momentary Latching	1NO1NC	RJS102P-16L-F-R~67Q RJS102P-16LA-F-R~67Q	BS - BRUSHED STEEL BLK - BLACK ANODISED ALLUMINIUM NP - NICKEL PLATE CUSTOM FINISHES AVAILABLE *SUBJECT TO MOQ	R Red G Green Y Yellow W White B Blue O Orange	AC:250V/3A DC: 12V/1A LED <20mA
	With LED	Momentary Latching	1NO1NC	RJS102P-16L-H-R~67Q RJS102P-16LA-H-R~67Q			
	With LED	Momentary Latching	1NO1NC	RJS102P-16L-F-D~67Q RJS102P-16LA-F-D~67Q			
	With LED	Momentary Latching	1NO1NC	RJS102P-16L-B-D~67Q RJS102P-16LA-B-D~67Q			
	With LED	Momentary Latching	1NO1NC	RJS102P-16L-F-C1~67Q RJS102P-16LA-F-C1~67Q			

DRAWING

IP67 		IP67 	
IP67 		IP67 	
IP67 			

RJS102P-16L SERIES

LED METAL SWITCH



SPECIFICATIONS

Contact parameters	Contact configuration	1NO1NC
	Contact	Silver alloy,Pin terminal
Color/voltage	Optional color	R O Y G B W
	Optional voltage	0V 5V 12V 24V
Other parameters	Mechanical life	200,000cycles
	Electrical life	50,000cycles
	LED life	40,000hour
	Terminal Type	Pin Terminal(2.8X0.5)
	Contact resistance	≤50mΩ
	Insulation resistance	≥1000mΩ
	Dielectric Strength	2000VAC
	Operation Temperature	-20°C~+55°C

SELECTOR GUIDE

RJS102P

SIZE:

16L - 16MM

HEAD:

B - Ball Head
F - Flat Head
H - High Head

LED TYPE:

R - Ring LED
D - Dot LED
C1 - Power
Symbol LED
X - Custom
Symbol
*subject to MOQ

LED COLOUR:

R - Red
B - Blue
G - Green
Y - Yellow
W - White
O - Orange

FINISH:

BS - Brushed Steel
NP - Nickel Plate
BLK - Black Anodised
Aluminium

LED VOLTAGE:

0V - 0 Volt
5V - 5 Volt
12V - 12 Volt
24V - 24 Volt

IP RATING:

67Q - IP67

Wiring available subject to MOQ
Contact us for more information!
+44 (0) 1234 213600 | sales@rjselectronics.com

