

## ■ Non-Illuminated

Appearance	Part Number	Contact	Function	Crust Material	Colour	Rated Voltage / Current
	RJS103-25L(A)-F-R-67Q RJS203-25L(A)-F-R-67Q	1NO1NC/ 2NO2NC	Momentary / Latching	Stainless Steel Black Anodised Aluminium	<b>R</b> Red <b>G</b> Green <b>Y</b> Yellow <b>W</b> White <b>B</b> Blue <b>O</b> Orange	LED Non-resisted (1.8-3V) Resisted 5V/12V/24V 110VAC/250VAC
	RJS103-25L(A)-F-D-67Q RJS203-25L(A)-F-D-67Q	1NO1NC/ 2NO2NC	Momentary / Latching			
	RJS103-25L(A)-F-C5-67Q RJS203-25L(A)-F-C5-67Q	1NO1NC/ 2NO2NC	Momentary / Latching			
	RJS103-25L(A)-F-C1-67Q RJS203-25L(A)-F-C1-67Q	1NO1NC/ 2NO2NC	Momentary / Latching			

## ■ Drawings

<p>IP67</p> <p>RJS103-25L(A)-F-R-67Q</p>	<p>Technical drawing showing dimensions: <math>\phi 19.6</math>, <math>\phi 15.5</math>, M2.5X1, 13.8, 6.9, 19, 17.2, 17.8, 1.5, <math>\phi 28</math>, 28, L.</p>	<p>IP67</p> <p>RJS103-25L(A)-F-D-67Q</p>	<p>Technical drawing showing dimensions: <math>\phi 19.5</math>, <math>\phi 9.2</math>, M2.5X1, 13.8, 6.9, 19, 17.2, 17.8, 1.5, <math>\phi 28</math>, 28, L.</p>
<p>IP67</p> <p>RJS103-25L(A)-F-C5-R-67Q</p>	<p>Technical drawing showing dimensions: <math>\phi 19.6</math>, <math>\phi 15.5</math>, M2.5X1, 13.8, 6.9, 19, 17.2, 17.8, 1.5, <math>\phi 28</math>, 28, L.</p>	<p>IP67</p> <p>RJS103-25L(A)-F-C5-67Q</p>	<p>Technical drawing showing dimensions: <math>\phi 19.5</math>, <math>\phi 9.2</math>, M2.5X1, 13.8, 6.9, 19, 17.2, 17.8, 1.5, <math>\phi 28</math>, 28, L.</p>