

RJSAS22E Keylock Switches



Features

IP20(IEC60529)(IP65)
IEC60947-5-1 K)。
(IEC60947-5-5 ; 6.2)。


Contact Ratings

Rated insulation voltage		600V			
Rated current		10A			
Rated voltage		24V	120V	240V	380V
AC (50/60Hz)	(AC-12)	10A	10A	6A	2A
	(AC-15)	10A	6A	3A	1.9A
DC	(DC-12)	8A	2.2A	1.1A	-
	(DC-13)	4A	1.1A	0.55A	-

Specifications

Operating Temperature	-20~+55°C		
Operating Humidity	45-85%		
Store Temperature	-45~+80°C		
Store Humidity	95%RH		
Degree of Protection	IP65(IEC 60529) IP20(IEC 60529)		
Insulation Resistance	100MΩ (500V DC)		
Dielectric Strength	2,500VAC/1		
	2,000VAC/1		
Vibration Resistance	10~500Hz	0.35mm	50m/s ²
	10~500Hz	0.35mm	50m/s ²
	5~55Hz 30Hz	0.5mm 1.5mm	
Shock resistance	150 m/s ²		
	1,000 m/s ²		
	100 m/s ²		
	1,000 m/s ²		
Mechanical Life	250,000		
	5,000,000		
	1,000,000		
	250,000		
	100,000		
	250,000 100 000		
Electrical Life	100,000		
	50,000		

How to Order






RJSAS22E Keylock Switches

Keylock Positions

/Sort	Reset Style				Key out Positon						
	Maintained	Momentary									
3Positon	⊗	⊙			⊗	⊗		⊙			
Code	2	0			A	B		D			
3Positon	⊕	⊙	⊙	⊙	⊗	⊗	⊗	⊙	⊙	⊙	⊙
Code	3	7	6	1	A	B	C	D	E	F	G

Selector/Key basic rotation angle 90°

Keylock Switches

Product appearance	Positions	Operation	Contact	Model
Key Switches 		Momentary	1NO	RJSAS22E -6110-0
			1NC	RJSAS22E -6101-0
			2NO	RJSAS22E -6120-0
			2NC	RJSAS22E -6102-0
			1NO+1NC	RJSAS22E -6111-0
		Maintained	1NO	RJSAS22E -6110-2
			1NC	RJSAS22E -6101-2
			2NO	RJSAS22E -6120-2
			2NC	RJSAS22E -6102-2
			1NO+1NC	RJSAS22E -6111-2
		Maintained	2NO	RJSAS22E -7120-3
			2NC	RJSAS22E -7102-3
			1NO+1NC	RJSAS22E -7111-3

Drawing

