



Contact Ratings

Working voltage		24V	110V	220V
AC (50/60Hz)	Resistive	—	1.0A	0.5A
	Inductive	—	0.7A	0.5A
DC	Resistive	1.0A	0.2A	—
	Inductive	0.7A	0.1A	—

LED Ratings

Rated Voltage	Current
5V DC $\pm 5\%$	8mA AC: A, R, W, Y: 8mA G, S: 7mA
6V AC/DC ($\pm 10\%$)	DC: A, R, W, Y: 6mA G, S: 5mA
12V AC/DC ($\pm 10\%$)	AC: 9mA DC: 8mA
24V AC/DC ($\pm 10\%$)	AC: 9mA DC: 8mA

How to Order

RJSPS1622A	—						
		Operation Style	Operation Characteristic	Contact Structure	Colour	Voltage	Border color
		Indicator Momentary Maintained Selector (2P) Selector (3P) Key Switch (2P) Key Switch (3P)	Round Square Rectangle Round (LED) Square (LED) Rectangle (LED)	Nil SPDT(1a+1b) DPDT(2a+2b)	 Red  Green  Yellow  White  Blue  Orange	24VDC 12VDC 6.3VDC 110VAC 220VAC	Border GK: Black Border

Specifications

Degree of Protection	IP 65 Watertight /Oiltight
Contact Configuration	Single Pole, Double Pole
Maximum Voltage	250V AC/DC
Thermal Current	5A
Minimum Applicable Load	5V AC/DC, 1mA
Contact Material	Gold-plated silver
Terminal Style	.110" Solder/Quick Connect
Operating Temperature	-25°C to +55°C
Operating Humidity	45 to 85% RH
Contact Resistance	50M Ω maximum
Insulation Resistance	100M Ω minimum (500V DC megger)
Vibration Resistance	10 to 55Hz, amplitude 1.2mm p-p
Degree of Protection	>10g
Electrical Life	100,000 operations minimum (at full rated load)
Mechanical Life	Maintained: 1,000,000 operations minimum Momentary: 1,000,000 operations minimum Selector/Keylock: 250,000 operations minimum
Dielectric Strength	Switch Unit: 2,000V AC, 1min. between live/dead part and terminals of different poles; 1,000V AC, 1 minute between terminals of the same pole; 1,500V AC, 1 minute between contact and lamp terminals. Illumination Unit: 2,000V AC, 1min. between live Part/ground
Soldering Temperature	20W/5 Seconds or 260C/3 seconds

LED Indicators

Product appearance

Top Colour

Rated Voltage

RJSPS1622A Round



RJSPS1622A Square



RJSPS1622A Rectangle



 Red	24VDC
 Green	12VDC
 Yellow	6.3VDC
 White	110VAC
 Blue	220VAC
 Orange	